



Original Application Based on

Docket 75036CES

Inventors: Dale Frederick McIntyre and Dana Whitney Wolcott

**HYBRID CAMERA SYSTEM WITH ELECTRONIC ALBUM  
CONTROL**

I hereby certify that this correspondence  
is being deposited **today** with  
the United States Postal Services as  
"Express Mail--Post Office to Addressee"  
and is addressed to:

Assistant Commissioner for Patents,  
ATTN: BOX PATENT APPLICATION  
Washington, D. C. 20231

Express Mail Label No.: EM026533789US

Date of Mailing: February 20, 1997

Signature: Diane Nesbitt

Name: Diane Nesbitt

HYBRID CAMERA SYSTEM WITH ELECTRONIC ALBUM CONTROLFIELD OF THE INVENTION

5 This invention relates to hybrid camera systems capable of capturing both electronic and photographic film images, and more particularly to a hybrid camera system, method and apparatus for selectively reviewing and creating album formats for film images captured by the camera.

BACKGROUND OF THE INVENTION

10 Hybrid cameras that concurrently capture both photographic film and electronic images of a scene are shown in U.S. Patent No. 4,716,470, which describes a hybrid camera containing systems for capturing  
15 respective images onto a photographic film and an electronic imaging element, such as an area array of charge coupled devices (CCD). The camera has an optical system, in combination with a shutter release mechanism, allowing a still image to be captured by the photographic film and the electronic imaging element,  
20 either sequentially using a single optical system or essentially simultaneously using parallel optical systems.

25 Hybrid cameras also may include a display, usually a liquid crystal display (LCD) provided in the rear of the camera which allows the user to either review or preview the image. The user then may opt to process the captured photographic image based on the still electronic image, or in the review mode, the user may alternately decide not to process the reviewed image as  
30 captured on the photographic film. Such a hybrid camera is described in U.S. Patent No. 4,742,369 in which the user is given an option as to whether to preview a selection after electronic image capture or review after the photographic and electronic images

08802548-022097

2

5

**10**

15

20

25

30

35

3

disclosure of the present invention. The use of the magnetic tracks has found a number of useful applications, particularly relating to the photoprocessing field. For further information on cameras having magnetic tracks, see U.S. Patent No. 5,023,635, which describes a camera having a dual capture system which includes a video monitor which is used in writing photo finishing instructions onto the magnetic track of the film.

Schemes have been proposed for magnetically recording on the photographic film information useful in organizing photographs in an album. For example, information recorded may represent a series of album pages which have been preselected by a previewer and written onto the magnetic layer of the film, thereby allowing the user to select both the image and the desired page as well as the position of the print on the page of interest. However, the recording is made upon processing and is placed on the film upon return of the photographic order from the film processor. One of these album organization schemes is disclosed in U.S. Patent No. 5,274,418, which describes optically encoding information onto a filmstrip for orienting an array of processed images onto an album page. This patent, however, does not describe a camera having an electronic display or viewfinder to review prints to orient the captured images for presentation within an album format.

The creation of a meaningful album of photographs is also enhanced by a system embodying the invention which enables combination of textual information, such as screen-related data or other information, in addition to date stamping, with the photographic prints selected for album formatting in order to provide text on the same album pages as the prints of a processed order.

4

03803548-022097

SUMMARY OF THE INVENTION

A primary object of the present invention is to provide an improved system which increases the capability of hybrid cameras.

5 Another primary object of the present invention is to provide an improved hybrid camera system which allows a user to select images captured using a hybrid camera and determining a specific page and orientation onto which a selected image will be produced in an  
10 album-like format.

Another primary object of the present invention is to provide an improved hybrid camera system which allows a user to select a particular image in a particular order for composing the album pages which  
15 can be composed automatically by the photo processor.

A further object of the present invention is to provide an improved hybrid camera having the ability to magnetically record text annotation via voice  
20 recognition, keyboard, or other input means and to transfer the information so that the processor can create an album where the annotation is combined with the prints.

Briefly described, a hybrid camera system embodying the invention has image capture means, such  
25 as an electronic sensor and an optical and film transport mechanism, which simultaneously capture an optical image onto a photographic film and corresponding electronic image on the electronic sensor within a camera housing.

30 A display means can display the image captured electronically by the image capture means. In order to facilitate organization of prints made from the film into an album, input means are operated by the user

5

5 while observing the electronic image to selectively input album related instructions relating to the image displayed. The instructions can provide information or relate to the orientation and formatting of the prints in an album or album-like format.

10 In a preferred embodiment, the film has a magnetic recording media and the user selections are recorded directly onto the magnetic media allowing the selections to be read by photoprocessing apparatus capable of digitally reproducing the film images selected in the selected order and automatically composing the album pages to comprise the photographing order.

15 The invention also provides a method for selectively captured images in an album-like format using a hybrid camera having a display for displaying a captured image. In carrying out the method an image is simultaneously captured onto a photographic film and electronic imager or sensor contained with the camera.  
20 The film has a magnetic media for receiving information thereon. The captured image is then displayed. Thereafter, album related data is selectively inputted onto the magnetic media of film corresponding to the displayed image.

25 An advantage of the present invention is to provide for automatic creation of an album which satisfies the need to organize photographs without the necessity of two separate events, a first picture taking event and a later album making event. An album making event can become burdensome because the specific  
30 details of the picture taking event have become lost over time. the camera system of the present invention on the other hand, allows for capturing an image, previewing the image in an album format, supplying  
35 orientation and other formatting instructions for

08803648 10209

6

encoding onto the magnetic track, and selectively providing text annotation corresponding to the previewed image.

Another advantage of the present invention is that all of the proceeding steps can be done by the user and at the camera level, as opposed to having some of the steps performed at the photo finisher level. Another advantage of the present invention is that customization of images captured by the camera (i.e. orientation, fonts used, etc.) in an album-like format can be done at the time of the picture taking event using the camera and by writing directly onto the film. The photographs can then be produced at a later date by the photo finisher without further intervention of the photographer required

Other objects, features, and advantages will be apparent from the following Detailed Description of the Invention, when read in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a rear view of a camera according to a preferred embodiment of the present invention;

FIG. 2 is a diagrammatic side view of the camera of FIG. 1 illustrating dual image capture paths;

FIG. 3(a) is a diagrammatic view of the rear of the camera of FIGS. 1 and 2, including electronic imaging and text displays and controls;

FIG. 3(b) is an alternate display for use with the camera of FIGS. 1 and 2;

FIG. 4 is a diagrammatic view showing other input features as displayed in the text display of FIG. 3(A);

08803648 02209

7

FIG. 5 is a control block diagram of the camera of FIGS. 1-4;

5 FIG. 6 is a flow chart of the logic used to select and process album decisions and annotation using the camera of FIGS. 1-5;

FIGS. 7(a) and 7(b) are flow charts of the photoprocessing logic used with the camera of FIGS. 1-6 for culling out and printing orders selected and for processing album decisions and annotation;

10 FIG. 8 is a display selection of possible album page layouts showing different orientations and sizes for selection by a user;

15 FIG. 9 is a block diagram of the interface between the electronic display and the electronic imager of the described embodiment;

FIG. 10 is a partial sectional view of the camera of FIG. 1, taken through line 10-10; and

20 FIG. 11 is a partial top view of the magnetic layer of a photographic filmstrip used in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

25 This invention is now described in relation to a preferred embodiment using a specific non-single lens reflex (NSLR) hybrid camera. It will be apparent from the following discussion, however, that the teachings of the present invention can extend to SLRs, as well as other known cameras, including digital cameras, which can also be adapted in a similar fashion.

30 FIGS. 1 and 2 show a non-single-lens-reflex camera 10 which includes a rectangular camera housing or body 12 having an optical viewfinder 13. The optical

0803548 02097 150220" 8450380

8



20

35

5 Therefore, further discussion is not required, except  
as needed.

10

25

30

35

202 onto which the exposed film 204 is wound. When all frames have been exposed, a film rewind mechanism (not shown) rewinds the exposed film 204 from the take-up spool 202 back onto the confines of the film cartridge 180, as is conventionally known. The workings themselves of the so-called "thrust-type" cartridges, as well as those of the film advance and take-up mechanisms are commonly known in the prior art and do not form a basis for the present invention.

Referring to FIGS. 2, 10 and 11, a magnetic head 40 is fixedly disposed along the film travel path 195 in a location adjacent one of the longitudinal magnetic tracks 186 of the passing filmstrip 182. The magnetic head 40 is capable of recording information to one of the magnetic tracks 186 based on specific data input by the camera user, as ~~described in~~ <sup>described in</sup> greater detail below. As more clearly illustrated in FIG. 2, camera 10 includes dual film and electronic image capture systems. A length of the photographic filmstrip 182 corresponding to a track 186 is advanced from the film cartridge 180, and into the exposure gate 198, of the camera body 12. Upon depression of the shutter release button 18, ambient light is passed through an objective imaging lens 30 which focuses the light through a shutter aperture 32 along an optical axis 42 into the exposure gate 198, FIG. 10, and onto a film plane 28, in a manner commonly known in the ~~field~~ <sup>field</sup> filed.

Similarly, a solid-state imaging element or imagery 34, such as a charge coupled device (CCD), is adjacently and fixedly positioned by known means within the interior of the camera body 12 to receive an optical image as focused by a separate focusing lens 38 through a shutter aperture 36 along a parallel optical axis 44. According to this embodiment, and as described below, each of the shutter apertures 32, 36

are opened essentially simultaneously by the depression of the shutter release button 18.

5 The specific positioning of the electronic imager 34 and the workings of the shuttering mechanism (not shown) are not necessarily critical to the workings of the present invention, provided the dual optical systems are configured and aligned to capture essentially the same scene as viewed through the optical viewfinder 13. A similar system is described in commonly assigned U.S. Patent No. 4,949,117, which is hereby incorporated by reference into the disclosure of the present invention. In addition, it is also contemplated for purposes of the present invention that a single optical path can be utilized in lieu of using a pair of optical systems by using a beamsplitter or other similar device. Such an arrangement is described in U.S. Patent No. 4,716,470 which is hereby incorporated by reference into the disclosure of the present invention. Other salient features of the present camera 10 will now be described.

Referring to the block diagram of FIG. 5, hybrid camera 10 includes a contained microprocessor 68; for example, an 8-bit or 16-bit microprocessor such as Model MC68HC11, manufactured by Motorola Corporation, having sufficient logic for interconnecting each of the operational components or control blocks, including an autofocus block 70, a lens control block 72, an autoexposure block 74, a flash control block 76, and a timer block 78, respectively, shown herein for completeness. Additional details relating to each of the above control blocks are found in U.S. Patent No. 4,949,117. Otherwise, for purposes of the present invention, no further discussion is supplied herein, except as needed.

Still referring to FIG. 5, and particularly to the present invention, the microprocessor 68 also controls each of the imaging and textual displays 20, 24 through an electronic display control block 88. In addition, an annotation control block 82 supplies text input through the back and white display 24 via an annotation input path 80 which loads the text information for writing onto the magnetic layer 184 of the filmstrip 182, FIG. 11, and more specifically to a magnetic track 186 through an output data path 84 to the electrical interface circuitry block 86 controlling the magnetic head 40, FIG. 2.

An example of a useful electronic display control block 88 pertaining to the imaging display 20 is illustrated in FIG. 9. As is known in the field, an electronic liquid crystal display requires a video signal input, as opposed to computer LCDs which typically recognize digital signal input. Therefore, CCD driver circuitry 132 allows an electronic image to be captured by the photodiodes (not shown) of the image sensor 34, having appropriate analog signal processing circuitry and amplifying circuitry 134. A corresponding analog signal is converted to a digital signal by an analog-to-digital converter 136 and processed by a digital signal processor 138 prior to storage in a digital memory 140 using address generators 156. Additional conversion of the digital signal by a digital-to-analog converter 142 and NTSC converter 144 allows an NTSC video signal to be transmitted through signal conditioning electronics 146 for display by the LCD 20, preferably having a powered backlight 148 as is commonly known. A battery 150 powers microprocessor 68 via a voltage regulating block 152, the microprocessor also being interconnected to a high speed slave timing generator 154. Additional details relating to the processing of the image signal

13

0803548 02209

**5**

**10**

15

20

25

30

35

14

the image perceived by each of the imaging lenses 30,38. Depression of the shutter release button 18 causes simultaneous image capture by the photographic filmstrip 182 and the electronic imager 34 by opening of respective shutter apertures 32,36, <sup>in</sup> a commonly known manner. Automatically, the capture of the image on the electronic imager 34 enables the electronic display control block 88, as described above with reference to FIG. 9, to transmit a digitized version of the captured image onto the imaging display 20.

Initially, a corresponding user prompt message is transmitted by the microprocessor 68 through similar circuitry to the textual display 24, as shown more clearly in FIG. 3(a). The series of default prompts relate to the automatic album making function as displayed by the textual display 24 in a series of discrete fields. According to this embodiment, the initial display includes a query field 56, a query response field 58, an image sequence number 60 and a page break field 62, respectively, sequentially disposed across the single line text display 24. According to the present embodiment, the initial default parameters which are displayed by display 24 indicate to the user that the displayed image will be placed in an album. In addition, the corresponding frame number of the filmstrip 182 is assigned as the album order number with no defined page breaks as in each of the respectively displayed fields.

According to step 94 of FIG. 6, the user may elect to alter the present default parameters by depressing the control button 50 until the query response field 58 is flashing. For example, if the user does not desire to place a displayed image in an album, then depression of either of the scroll buttons 52, 54 increments the query response to NO. This election is confirmed by subsequent depression of the control button 50. Non-

15

080349 0209 460220 845E0880

election of the automatic album feature shifts the software to step 104 and the filmstrip 182 is readied for subsequent advance.

5 If the automatic album feature is selected, and according to step 96, the scrolling buttons 52,54 allow movement through a menu of available choices relating to the orientation and format of the displayed prints on album pages. These buttons can be used to prompt a set of alternate menu choices, as programmed into the logic of the microprocessor 68 in a commonly known manner. A convenient menu logic for the textual information according to this embodiment is a series of choices which are conveyed similarly to those used in a Microsoft Windows environment. One specific example of a formatting option is illustrated in FIG. 8, used for selecting the format of an album page. Depending on the memory available in the microprocessor 68, this option allows an operator to visually see several selected imagerettes on a number of album pages 130. In each case, an album related selection is stored in the volatile memory (not shown) of the microprocessor 68 after confirmation by depression of the control button 50. By scrolling in either menu direction, album format, orientation and page selections can be modified prior to adding of text annotation.

According to step 98, and after all of the album input parameters have been selected for a displayed image by the user according to the menu, depression of the control button 50 will trigger the microprocessor 68 to engage the annotation feature and the user will be initially prompted for input.

It should be noted that a number of different means for inputting appropriate text information can be utilized. For example, U.S. Patent No. 4,742,369

16

080548-02007



describes a voice recognition system for a camera that can be modified to provide the necessary input. Alternately, the 4,742,369 patent also describes an alphanumeric keypad which can be used in conjunction with the present invention according to the annotation input path 80 shown in FIG. 5. Cameras such as the Ricoh RZ-105 also include a keypad inputting feature. The specific input device is not critical to the present invention; therefore, other similar devices can be used.

An initial text display 24 is depicted in FIG. 4. As shown, and depending on the logic contained in the microprocessor 68, a variety of menu options are available. According to the present embodiment, the font style and size of the annotated text information that the photo finisher will use on the selected album pages can be preselected in a font control field 66 by the user and written onto the magnetic layer 184, FIG. 11, of the filmstrip 182, FIG. 11. As in the album formatting and orientation steps, scroll buttons 52, 54 can be used to prompt a set of alternate menu choices, as programmed into the logic of the microprocessor 68 in a commonly known manner for confirmation by depression of the control button 50. As noted above, a convenient menu logic for the textual information according to this embodiment is a series of choices which are similar to those used in a Microsoft Windows environment. Still referring to FIG. 4, the text LCD display 24 is also an advantageous way of displaying the results of annotation input for caption text used on the album page corresponding to the selected image, also by election of the user by depression of the button 50 using electronic display control block 88, in a manner previously described.

According to step 100, the input annotation data is then written onto the magnetic tracks 186 of the

17

08003548 022097

contained photographic filmstrip 182 using output data path 84 and the interface magnetic head circuitry 86 of FIG. 5. A preferable scheme is contained in commonly assigned U.S. Patent No. 5,450,149 which is hereby  
5 incorporated by reference into the disclosure of the present invention.

According to step 102, and if no textual information was written onto the filmstrip 182, or if annotation is completed, then the filmstrip can be  
10 advanced using the film advance mechanism (not shown), the features of which are commonly known in the field. Alternately, if no annotation was selected, or if the automatic album feature was not selected, then the film can be advanced.

According to step 104, and once the filmstrip has been advanced to the next frame, the LCD information display indicates the camera 10 is ready for another imaging sequence and steps 90-104 are repeated.  
15 Depending on the amount of memory available to the microprocessor 68, the user can repeatedly scroll  
20 through the displayed images stored in memory prior to unloading the film cartridge 180 from the camera body 12. For example, the microprocessor 68 can be programmed to store all captured images, whether or not  
25 album related data has been correspondingly written onto the film 182.

FIGS. 7(a) and 7(b) depict flow diagrams of the logic used by the microprocessor 68 to automatically print the album pages during the photofinishing  
30 process. After the photographic film 204 has been rewound into the confines of the film cartridge 180, and removed from the camera body 12, the film cartridge is delivered to a photo processor. A high resolution scanner (not shown) is preferably used to scan the  
35 negatives. Prior to or during the scanning process,

18

08803548 1022097

the designated magnetic tracks 186 of the exposed film 204 are read by the photofinishing apparatus (not shown) to determine if the automatic album feature is present. According to step 110, and if the automatic album feature is not present on the magnetic layer 184 of the exposed photographic film 204, then standard photofinishing will occur. According to step 112, and if the automatic album feature is detected, then photofinishing apparatus, (not shown) connected to a computer network (not shown), creates a folder/path on an attached file server. The images, annotated text, and attached album directions are then digitally scanned according to step 114. According to step 116 and after the images have been scanned, the photofinishing apparatus creates an Image Pack for albuming and according to step 118 transfers it along with the album composition data to the newly created folder on the file server. According to step 120, a workstation (not shown) also attached to the file server executes software that takes the image pack along with the album composition data to display on the workstation's video display terminal (VDT) (not shown). According to step 122, the workstation operator then inspects the pages and corrects for any orientation problems per step 124. If any orientation problems are present, then they are fixed according to step 126. Otherwise, finished album pages are printed when the softdisplay VDT looks appropriate.

While the invention has been described with reference to a preferred embodiment, it will be appreciated that various modifications can be made without departing from the spirit and scope of the invention. Such modifications are intended to fall within the scope of the appended claims.

19

08803548 022097

**PARTS LIST FOR FIGS. 1-11**

10	camera
12	camera body
13	optical viewfinder
5 14	top surface
15	front side
16	LCD information display
18	shutter release button
20	electronic imaging display
10 22	rear side
24	textual display
28	photographic film plane
30	film imaging lens
32	film shutter/aperture
15 34	solid-state imager
36	imager shutter/aperture
38	imager focusing lens
40	magnetic head
42	optical axis
20 44	optical axis
48	electronically displayed image
50	control button
52	scroll forward/increment button
54	scroll backward/decrement button
25 56	query field
58	query response field
60	image sequence number
62	page break field
64	composite electronic display
30 66	font control field
68	microprocessor
70	autofocus block
72	lens control block
74	autoexposure block
35 76	flash block
78	timer block
80	annotation input path
82	annotation control block
84	output data path block
40 86	magnetic head interface circuitry block
88	electronic display control block
90-128	steps
130	album formats
132	CCD driver
45 134	analog signal processor
136	A/D converter
138	digital signal processor
140	digital memory
142	D/A converter
50 144	NTSC converter
146	LCD signal preparation and drivers block
148	LCD and backlight

	150	battery
	152	voltage regulator block
	154	high speed slave timing regulator
5	180	film cartridge
	182	filmstrip
	184	magnetic layer
	185	perforation
	186	magnetic tracks
	188	edges
10	190	film frame
	192	cartridge receiving chamber
	194	cartridge spool
	195	film travel path
	198	film exposure gate
15	200	film roll chamber
	202	take-up spool
	204	exposed film